FACT SHEET

as required by LAC 33:1X.3111, for draft Louisiana Pollutant Discharge Elimination System Permit No. LA0058882 to discharge to waters of the State of Louisiana as per LAC 33:1X.2311.

The permitting authority for the Louisiana Pollutant Discharge Elimination System (LPDES) is:

Louisiana Department of Environmental Quality

Office of Environmental Services

P. O. Box 4313

Baton Rouge, Louisiana 70821-4313

I. THE APPLICANT IS: 0

CECOS International, Inc.

Calcasieu Facility P. O. Box 1849 Sulphur, LA 70664

II.

PREPARED BY:

Paula M. Roberts

DATE PREPARED:

July 10, 2006

III.

PERMIT ACTION:

renewal of LPDES permit LA0058882/AI 276

LPDES application received: June 30, 2004

IV. <u>FACILITY INFORMATION:</u>

- A. The application is for the intermittent discharge of stormwater runoff from the inactive closed and capped landfill cells and undeveloped areas from an existing industrial waste disposal facility.
- B. The facility is located at 918 Willow Springs Road, four miles east of LA Hwy. 27 and five miles north of Westlake; Calcasieu Parish, Louisiana.
- C. This facility is an aqueous industrial waste disposal facility that utilizes deep well injection to dispose of aqueous industrial wastes received from off-site and aqueous waste generated onsite.

The stormwater runoff can be classified into three groups: 1) runoff from areas associated with the active on-site disposal well; 2) runoff from the closed and capped landfill cells; and 3) runoff from undeveloped areas. All runoff associated with the disposal well is contained and injected into the on-site disposal well.

There is secondary containment around the scales, and the Tank area that includes tank – T-1 through T-9, and TT-1, and TT-2, as well as the chemicals and materials contained on site. Any runoff from these areas are sent to the injection well. About 2000 gallons of leachate are accepted each month.

<u>Definition</u>: Aqueous - something made up of water; relating to, like, containing, or dissolved in water; watery.

D. The LAC references are the legal references while the 40 CFR references are presented for information purposes only. In most cases, LAC language is based on and is identical to the 40 CFR language. 40 CFR Parts 401-402, and 405-471 have been adopted by reference at LAC 33;IX.4903 and will not have dual references. In addition, state standards LAC 33.IX.Chapter 11) will not have dual references.

<u>LAC 33:IX.Citations</u>: Unless otherwise stated, citations to LAC 33:IX refer to promulgated regulations listed at Louisiana Administrative Code, Title 33, Part IX.

<u>40 CFR Citations</u>: Unless otherwise stated citations to 40 CFR refer to promulgated regulations listed at Title 40, Code of Federal Regulations in accordance with the dates specified at LAC 33:IX.4901, 4903, 2301.F.

<u>Technology Based Effluent Limitations and Conditions:</u> Regulations promulgated at LAC 33:1X.2707.A/40 CFR Part 122.44 (a) require technology-based effluent limitations to be placed in LPDES permits based on effluent limitations guidelines where applicable, on BPJ(best professional judgment) in the absence of guidelines, or on a combination of the two.

<u>Guideline</u>

Reference

None

None

Other Sources of technology based limits:

LDEQ Stormwater Guidance, letter dated 6/17/87, from J. Dale Givens (LDEQ) to Myron Knudson (EPA Region 6)
Best Professional Judgment

E. Outfall 001

Discharge Location:

Latitude 30° 19 ' 18" North

Longitude 93° 18' 02" West

Description:

stormwater runoff from inactive (closed and capped cells)

(intermittent)

Design Flow:

variable

Outfall 002

Discharge Location:

Latitude 30° 19′ 20″ North

Longitude 93° 18' 27" West

Description:

stormwater runoff from inactive (closed and capped cells)

(intermittent)

Design Flow:

variable

Outfall 003

Discharge Location:

Latitude 30° 19′ 05" North

Longitude 93° 18' 01" West

Description:

stormwater runoff from inactive (closed and capped cells)

(intermittent)

Design Flow:

variable

V. RECEIVING WATERS:

The discharge from Outfall(s) 001 and 002 is from an effluent pipe into an unnamed drainage ditch, thence into Little River in segment 030804 of the Calcasieu River Basin. The discharge from Outfall 003 flows from an effluent pipe into an unnamed ditch, thence into West Fork Calcasieu River in segment 030801 of the Calcasieu River Basin. These two segments are both listed on the 303(d) list of impaired waterbodies.

This facility only discharges non-contact stormwater runoff, Water Quality Based Effluent Limitations will not be calculated for this facility, therefore, values for the critical low flow (7Q10), harmonic mean flow, hardness (CaCO₃), and the fifteenth percentile were not requested.

The designated uses and degree of support for Segment 030804 of the Calcasieu River Basin are as indicated in the table below.¹:

Overall Degree of Support for Segment 030804		Degree of Support of Each Use								
Partial	Primary Contact Recreation	Secondary Contact Recreation	Propagation of Fish & Wildlife	Outstanding Natural Resource Water	Drinking Water Supply	Shell fish Propagation	Agriculture			
	Full	Full	Not	N/A	N/A	N/A	N/A			

¹The designated uses and degree of support for Segment 030804 of the Calcasieu River Basin are as indicated in LAC 33:IX.1123.C.3, Table (3) and the 2002 Water Quality Management Plan, Volume 5, Part'B, Water Quality Inventory respectively.

The designated uses and degree of support for Segment 030801 of the Calcasieu River Basin are as indicated in the table below. It

Overall Degree of Support for Segment 030801	Degree of Support of Each Use .								
Full	Primary Contact Recreation	Secondary Contact Recreation	Propagation of Fish & Wildlife	Outstanding Natural Resource Water	Drinking Water Supply	Shell fish Propagation	Agriculture		
	Full	Full	Not	N/A	N/A	N/A	Full		

The designated uses and degree of support for Segment 030801 of the Calcasieu River Basin are as indicated in LAC 33:IX.1123.C.3, Table (3) and the 2002 Water Quality Management Plan, Volume 5, Part B, Water Quality Inventory respectively.

Subsegment 030804, Little River-Headwaters to West Fork Calcasieu River, is listed on LDEQs Final 2004 305(b)/303(d) Integrated Report as impaired for Mercury and was once listed as impaired for Dissolved Oxygen. The Little River Watershed TMDL for Oxygen-Demanding Substances including a Watershed Nonpoint Source Load Allocation (Subsegment 030804) was finalized on March 15, 2002. To date no TMDLs have been established for this waterbody to address Mercury. A reopener clause will be established in the permit to allow for the requirement of more stringent effluent limitations and requirements as imposed by a TMDL.

According to the Little River Watershed TMDL for Oxygen-Demanding Substances, subsegment 030804 was void of any known oxygen-demanding point source discharges. The Cecos facility was acknowledged and documented but not included in the model.

Subsegment 030801, West Fork Calcasieu River-From confluence of Beckwith Creek and Hickory Branch to Calcasieu River, is listed on LDEQs Final 2004 305(b)/303(d) Integrated Report as impaired for Mercury and was once listed as impaired for Dissolved Oxygen. The TMDL for Dissolved Oxygen for the Calcasieu Estuary (Subsegments 030305, 030801, 030901, and 031001 was finalized on July 1, 2002. To date no TMDLs have been established for this waterbody to address Mercury. A reopener clause will be established in the permit to allow for the requirement of more stringent effluent limitations and requirements as imposed by a TMDL.

According to the TMDL for Dissolved Oxygen for the Calcasieu Estuary, under summer critical conditions, the D.O. criteria for all subsegments were attained through reductions in nonpoint source loadings, except Bayou D'Inde. Under winter conditions, the DO criteria in Contraband Bayou and West Fork/Houston River were attainable through reductions in nonpoint source loadings.

The effluent data for Mercury submitted with the application, reported there was no excursion above the required minimum quantification level (MQL).

This facility discharges only stormwater runoff from three outfalls during rainfall events, it is unlikely, that this discharge will contribute to the Mercury impairment or contribute to the dissolved oxygen conditions in the receiving stream, therefore, there are no reductions or additional limitations imposed in this permit for these parameters. However, monitoring for Mercury is included in this permit as a part of the previous permit limitations.

VI. ENDANGERED SPECIES:

The receiving waterbody(ies), Subsegment(s) 030801 and 030804 of the Calcasieu River Basin are not listed in Section II.2 of the Implementation Strategy as not requiring consultation with the U. S. Fish and Wildlife Service (FWS). This strategy was submitted with a letter dated October 21, 2005 from Watson (FWS) to Gautreaux (LDEQ). Therefore, in accordance with the Memorandum of Understanding between the LDEQ and the FWS, further informal (Section 7, Endangered Species Act) consultation is not required. It was determined that the issuance of the LPDES permit is not likely to have an adverse effect on any endangered or candidate species or the critical habitat. The effluent limitations established in the permit ensure protection of aquatic life and maintenance of the receiving water as aquatic habitat.

VII. HISTORIC SITES:

The discharge is from an existing facility location, which does not include an expansion beyond the existing perimeter. Therefore, there should be no potential effect to sites or properties on or eligible for listing on the National Register of Historic Places, and in accordance with the "Memorandum of Understanding for the Protection of Historic Properties in Louisiana Regarding LPDES Permits" no consultation with the Louisiana State Historic Preservation Officer is required.

VIII. PUBLIC NOTICE:

The public notice is published in the local newspaper of general circulation and the Office of Environmental Services Public Notice Mailing List. Upon publication of the public notice, a public comment period shall begin on the date of publication and last for at least 30 days thereafter. During this period, any interested persons may submit written comments on the draft permit to the LDEQ contact person, listed below, and may request a public hearing to clarify issues involved in the permit decision. A request for a public hearing shall be in writing and shall state the nature of the issues proposed to be raised in the hearing.

Public notice published in:

Local newspaper of general circulation
Department of Environmental Quality Public Notice Mailing List

For additional information, contact:

Ms. Paula M. Roberts
Permits Division
Department of Environmental Quality
Office of Environmental Services
P. O. Box 4313
Baton Rouge, Louisiana 70821-4313

IX. PROPOSED PERMIT LIMITS:

The effluent limitations for the priority pollutants listed in the previous permit were based upon empirical data developed in the early 1980's for the regulation of toxic pollutants to hazardous waste facilities and sites with low potential stormwater.

The previous permit limits were also based upon technology-based effluent limitations, and according to the regulations promulgated at LAC 33:IX.2707.A/40 CFR Part 122.44(a) requires technology-based effluent limitations to be placed in LPDES permits based on effluent limitations guidelines where applicable, on BPJ (best professional judgment) in the absence of guidelines, or on a combination of the two.

OUTFALL(s) 001, 002, and 003

Final effluent limits shall become effective on the effective date of the permit and expire on the expiration date of the permit.

Final Effluent Limits:

Effluent Characteristic	Monthly Avg. (lbs./day)	Monthly Avg.	Daily Max	Basis
тос			50 mg/l	Multisector General Permit –Sector K.Table K-1 and previous permit limit
Oil & Grease			15 mg/l	Multisector General Permit-Sector K., Table K-1
Ammonia (NH ₃ -N)			19 mg/l	Multisector General Permit- Sector K., Table K-1
Total Phenols (4AAP)			500 ug/l	Previous permit limitation and BPJ
Metals & Cyanide				The following parameters are based upon the previous permit limitations and Best Professional Judgment
Total Antimony			600 ug/l	
Total Arsenic			100 ug/l	
Total Beryllium	ĺ		100 ug/l	
Total Cadmium			100 ug/l	
Total Chromium			200 ug/l	
Total Copper			500 ug/l	
Total Lead			150 ug/l	
Total Mercury			10 ug/l	
Total Nickel			500 ug/l	
Total Selenium			100 ug/l	
Total Silver			100 ug/l	
Total Thallium			100 ug/l	
Total Zinc			1000 ug/l	
Total Cyanide			100 ug/i	

Volatile Compounds			The following parameters are based
			upon the previous permit limitations and Best Professional Judgment
Acrolein		100 ug/l	und Dest Froressional Judgment
Acrylonitrile		100 ug/l	
Benzene		100 ug/l	·
Bromoform		100 ug/l	
Carbon Tetrachloride		100 ug/l	
Chlorobenzene	***	100 ug/l	
Chlorodibromomethane		100 ug/l	
Chloroethane		100 ug/l	
2-Chloroethly Vinyl Ether		100 ug/l	
Chloroform		100 ug/l	
Dichlorobromomethane		100 ug/l	
1,1-Dichloroethane		100 ug/l	
1,2- Dichloroethane		100 ug/l	
1,1-Dichlorethylene		100 ug/l	
1,2-trans- Dichlorethylene		100 ug/l	
1,2-Dichlorpropane		100 ug/l	
1,3-Dichloroporpylene		100 ug/l	
Ethylbenzene		100 ug/l	
Methyl Bromide		100 ug/l	
Methyl Chloride		100 ug/l	
Methylene Chloride		100 ug/l	
1,1,2,2- Tetrachloroethane		100 ug/l	
Tetrachloroethylene		100 ug/l	
Toluene		100 ug/l	•
1,1,1-Trichloroethane		100 ug/l	
1,1,2-Trichloroethane Trichloroethylene		100 ug/l 100 ug/l	
Vinyl Chloride		100 ug/l	
Acid Compounds		100 ug/1	
			The following parameters are based upon the previous permit limitations and Best Professional Judgment
2-Chlorphenol		100 ug/l	
2,4-Dichlorophenol		100 ug/l	
2,4-Dimethylphenol		100 ug/l	
4,6-Dinitro-o-Cresol		100 ug/l	
2,4-Dinitrophenol		100 ug/l	
2-Nitrophenol		100 ug/l	
4-Nitrophenol		100 ug/l	
Parachlormetacresol		100 ug/l	
Pentachlorphenol		100 ug/l	
Phenol		100 ug/l	<u> </u>
2,4,6-Trichlorophenol		100 ug/l	

Acenaphthene 100 ug/l	arameters are based is permit limitations ional Judgment
Anthracene	
Anthracene	
Benzo(a)anthracene	
Benzo(a)pyrene	
Benzo(b)fluoranthene	
Benzo(g,h,i)perylene	
Benzo(k)fluoranthene	
Bis(2-chlorethyl)ether 100 ug/l Bis(2-chlorethoxy)methane Bis(2-chloroisopropyl)ether Bis(2-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisopropyl)ether Bis(1-chlorisop	
Bis(2-chlorethoxy)methane	
Chlorethoxy)methane Bis(2- 100 ug/l 100 ug/l	
Chlòroisopropyl)ether Bis(2-	
ethylhexyl)phthalate	
Phenyl Ether Butyl Benzyl Phthalate 100 ug/l	
A-Chlorophenyl Phenyl Ether	
Phenyl Ether Chrysene 100 ug/l Dibenzo(a,h)anthracene 100 ug/l 1,2-Dichlorobenzene 100 ug/l 1,4-Dichlorobenzene 100 ug/l 3,3-Dichlorobenzidine 100 ug/l Diethyl Phthalate 100 ug/l Dimethyl Phthalate 100 ug/l Di-n-butyl Phthalate 100 ug/l 2,4-Dinitrotoluene 100 ug/l 2,6-Dinitrotoluene 100 ug/l Di-n-octyl Phthalate 100 ug/l Di-noctyl Phthalate 100 ug/l Fluoranthene 100 ug/l Fluoranthene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachlorocthane 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
Chrysene 100 ug/l Dibenzo(a,h)anthracene 100 ug/l 1,2-Dichlorobenzene 100 ug/l 1,3-Dichlorobenzene 100 ug/l 3,3-Dichlorobenzidine 100 ug/l Diethyl Phthalate 100 ug/l Dimethyl Phthalate 100 ug/l Di-n-butyl Phthalate 100 ug/l 2,4-Dinitrotoluene 100 ug/l 2,6-Dinitrotoluene 100 ug/l Di-n-octyl Phthalate 100 ug/l 1,2-Diphenylhydrazine 100 ug/l Fluorene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachloroethane 100 ug/l Isophorone 100 ug/l	
1,2-Dichlorobenzene	•
1,3-Dichlorobenzene	
1,4-Dichlorobenzidine	
3,3-Dichlorobenzidine	
Diethyl Phthalate	
Dimethyl Phthalate	
Di-n-butyl Phthalate 100 ug/l 2,4-Dinitrotoluene 100 ug/l 2,6-Dinitrotoluene 100 ug/l Di-n-octyl Phthalate 100 ug/l 1,2- 100 ug/l Diphenylhydrazine 100 ug/l Fluoranthene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorobutadiene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachloroethane 100 ug/l Ideno(1,2,3-cd) Pyrene 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
2,4-Dinitrotoluene 100 ug/l 2,6-Dinitrotoluene 100 ug/l Di-n-octyl Phthalate 100 ug/l 1,2- 100 ug/l Diphenylhydrazine 100 ug/l Fluorene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorobutadiene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachloroethane 100 ug/l Ideno(1,2,3-cd) Pyrene 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
2,6-Dinitrotoluene 100 ug/l Di-n-octyl Phthalate 100 ug/l 1,2- 100 ug/l Diphenylhydrazine 100 ug/l Fluoranthene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorobutadiene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachloroethane 100 ug/l Ideno(1,2,3-cd) Pyrene 100 ug/l Naphthalene 100 ug/l	
Di-n-octyl Phthalate	
1,2- 100 ug/l Fluoranthene 100 ug/l Fluorene 100 ug/l Hexachlorobenzene 100 ug/l Hexachlorobutadiene 100 ug/l Hexachlorocyclopenta diene 100 ug/l Hexachloroethane 100 ug/l Ideno(1,2,3-cd) Pyrene 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
Diphenylhydrazine	
Fluorene	
Hexachlorobenzene	
Hexachlorobutadiene	
Hexachlorocyclopenta diene	
diene 100 ug/l Hexachloroethane 100 ug/l Ideno(1,2,3-cd) Pyrene 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
Ideno(1,2,3-cd) Pyrene 100 ug/l Isophorone 100 ug/l Naphthalene 100 ug/l	
Isophorone	
Naphthalene 100 ug/l	
·	
Nitrobenzene 100 ug/i	<u></u>
100//	
N- Nitrosodimethylamine N-Nitododi-n 100 ug/l	

N-	Ţ	100 00/	
N- Nitrosodiphenylamine		100 ug/l	
Phenanthrene		100 ug/l	
Pyrene		100 ug/l	
1,2,4- Trichlorobenzene		100 ug/l	
Pesticides, and PCB's			The following parameters are based upon the previous permit limitations and Best Professional Judgment
Aldrin		10 ug/l	
Alpha-BHC		10 ug/l	
Beta-BHC		10 ug/l	
Delta-BHC		10 ug/l	
Gamma BHC (Lindane)		10 ug/l	
Chlordane	400	10 ug/l	
4,4-DDT		10 ug/l	
4,4-DDE		10 ug/l	
4,4-DDD		10 ug/l	
Dieldrin		10 ug/l	
Alpha-Endosulfan		10 ug/l	
Beta-Endosulfan		10 ug/l	
Endosulfan sulfate		10 ug/l	
Endrin		5 ug/l	
Endrin Aldehyde		10 ug/l	
Heptachlor		10 ug/l	
Heptachlor Epoxide		10 ug/l	
PCB's(Total)		*	
PCB-1016		*	
PCB-1221		*	
PCB-1232	_	*	
PCB-1242		*	
PCB-1248		*	
PCB-1254		*	
PCB-1260		*	
Toxaphene		10 ид/1	

^{*} There shall be no discharge of polychlorinated biphenyls (PCB's). The minimum quantification level for PCB's is 1.0 ug/l. If any individual analytical test result for PCB's is less than the minimum quantification level, then a value of zero (0) shall be used for the Discharge Monitoring Report (DMR) calculations and reporting requirements.

Other Effluent Limitations for Outfall 001

1) pH

In a report dated January 22, 1996, the permittee demonstrated that natural conditions of the soil proved to be highly acidic causing excursions in the 6-9 pH range. The previous permit contained a pH of not less than 5.5 standard units nor greater than 9.0 standard units. Therefore, through BPJ, the pH range has been retained from the previous permit.

2) Solids and Foam

There shall be no discharge of floating solids or visible foam in other than trace amounts in accordance with LAC 33:IX.1113.B.7.

X. <u>PREVIOUS PERMITS:</u>

LPDES Permit No. LA0058882: Issued: September 28, 1999

Effective: October 1, 1999 Expired: September 30, 2004

During the effective date of the permit and lasting through the expiration date of the permit.

Outfall 001, the intermittent discharge of inactive and undeveloped area stormwater from the northeastern portion of the site (estimated flow 0.12 MGD)

Outfall 002, the intermittent discharge of inactive and undeveloped area stormwater from the northeastern portion of the site (estimated flow 0.18 MGD)

Outfall 003, the intermittent discharge of inactive and undeveloped area stormwater from the northeastern portion of the site (estimated flow 0.014 MGD)

Effluent Characteristic	lbs./day	Discharge Lin	nitations (ug/l, unless sta	Monitoring Red	uirements
	Monthly	Monthly	Daily	Measurement	Sample
	Ayg.	Avg.	Max	Frequency	Туре
Flow	<u> </u>	Report	Report	1/ month	Estimate
TOC			50 mg/l	1/month	Grab
Ammonia (NH ₃ -N)			19 mg/l	1/month	Grab
Oil & Grease			15 mg/l	1/month	Grab
Total Phenol (4AAP)	-40		500	1/month	Grab
pH		5.5 (min)	6-9 (max)	1/day	Grab
P		` ′		•	
Metals and Cyanide					
Total Antimony			600	1/month	Grab
Total Arsenic			100	1/month	Grab
Total Beryllium			100	1/month	Grab
Total Cadmium			100	1/month	Grab
Total Chromium			200	1/month	Grab
Total Copper			500	1/month	Grab
Total Lead			150	1/month	Grab
Total Mercury			10	1/month	Grab
Total Nickel		***	500	1/month	Grab
Total Selenium			100	1/month	Grab
Total Silver			100	1/month	Grab
Total Thallium			100	1/month	Grab
Total Zinc			1000	1/month	Grab
Total Cyanide			100	1/month	Grab
Volatile Compounds					
Acrolein			100	1/year	Grab
Acrylonitrile			100	1/year	Grab
Benzene			100	1/year	Grab
Bromoform			100	1/year	Grab
Carbon Tetrachloride			100	1/year	Grab
Chlorobenzene			100	1/year	Grab

Fact Sheet CECOS International, Inc. – Calcasieu Facility LA0058882/AI 276/PER 20040002 Page 10

Effluent Characteristic	Dischare	ge Limitation	s	Monitoring Requ	irements
	lbs./day		≃ (ug/l, unless stated		in Cinicina
	Monthly	Monthly	Daily	Measurement	Sample
	Avg.	Avg.	Max	Frequency	Type
Chlorodibromomethane	<u> </u>		100	1/year	Grab
Chloroethane		594	100	1/year	Grab
2-Chlorethyl Vinyl Ether-			100	1/year	Grab
Chloroform			100	1/year	
Dichlorobromethane			100	•	Grab
1,1-Dichloroethane			100	1/year	Grab Grab
1,2-Dichloroethane		***	100	1/year	Grab
1,1-Dichloroethylene			100	1/year	Grab
1,2-trans-Dichloroethylene			100	1/year	
1,2-Dichloropropane				1/year	Grab
• •			100	1/year	Grab
1,3-Dichloropropylene			100	1/year	Grab
Ethylbenzene	B		100	1/year	Grab
Methyl Bromide			100	1/year	Grab
Methyl Chloride			100	1/year	Grab
Methylene Chloride			100	1/year	Grab
1,1,2,2-Tetrachloroethane			100	1/year	Grab
Tetrachlorethylene			100	1/year	Grab
Vinyl Chloride		770	100	1/year	Grab
Dichlorobromethane			100	1/уеаг	Grab
1,1-Dichloroethane	944		100	1/year	Grab
1,2-Dichloroethane			100	1/year	Grab
1,1-Dichloroethylene	•••		100	1/year	Grab
Acid Compounds				•	
2-Chlorophenol			100	16	Comb
			100	1/year	Grab
2,4-Dichlorophenol 2,4-Dimethyl phenol			100	1/year	Grab
			100	1/year	Grab
4,6-Dinitro-o-Cresol			100	1/year	Grab
2,4-Dinitrophenol			100	1/year	Grab
2-Nitrophenol 4-Nitrophenol			100	1/year	Grab
•			100	1/year	Grab
Parachlorometacresol			100	1/year	Grab
Pentachlorophenol Phenol			100 100	1/year	Grab
2,4,6-Trichlorophenol				1/year	Grab
2,4,0-1 (10)1010101101		***	100	1/year	Grab
Base Neutral Compounds					
Acenaphthene			100	1/year	Grab
Acenaphthylene			100	1/year	Grab
Anthracene			100	1/year	Grab
Benzidine			100	1/year	Grab
Benzo(a)anthracene			100	1/year	Grab
Benzo(a)pyrene			100	1/year	Grab
Benzo(a)fluoranthene			100	1/year	Grab
Benzo(g,h,i)perylene			100	1/year	Grab
Bis(2-chloroethyl) ether			100	1/year	Grab
Bis(2-chlorethoxy)methan	e		100	1/year	Grab
Bis(2-chloroisoprpoyl)ethe			100	1/year	Grab
Bis(2-chloroethyl) ether	~~~		100	1/year	Grab
4-Bromophenyl Phenyl Et	her		100	1/year	Grab

Fact Sheet CECOS International, Inc. – Calcasieu Facility LA0058882/AI 276/PER 20040002 Page 11

Effluent Characteristic	Discharge	: Limitations		Monitoring Rec	uirements
	lbs./day	other units	(ug/l, unless state		
	Monthly	Monthly	Daily	Measurement	Sample
	Avg.	Avg.	Max	Frequency	Type
Chrysene			100	1/year	Grab
Dibenzo(a,h) anthracene			100	1/year	Grab
1,2-Dichlorobenzene			100	1/year	Grab
1,3-Dichlorobenzene			100	1/year	Grab
1,4-Dichlorobenzene			100	1/year	Grab
3,3-Dichlorobenzene			100	· ·	Grab
Diethyl Phthalate			100	1/year	
•			100	1/year	Grab
Dimethyl Phthalate	***			1/year	Grab
Di-n-butyl phthalate			100	l/year	Grab
2,4-Dinitrotoluene			100	1/year	Grab
2,6-Dinitrotoluene		***	100	1/year	Grab
Di-n-octyl Phthalate		***	100	1/year	Grab
1,2-Diphenylhydrazine			100	1/year	Grab
Fluoranthene			100	1/year	Grab
Fluorene			100	1/year	Grab
Hexachlorobenzene			100	1/year	Grab
Hexachlorobutadiene		***	100	1/year	Grab
Hexachlorocyclopentadie	пе		100	1/year	Grab
Hexachlorethane			100	1/year	Grab
Ideno (1,2,3-cd)Pyrene			100	1/year	Grab
Isophorone			100	1/year	Grab
Naphthalene			100	1/year	Grab
Nitrobenzene			100	1/year	Grab
N-Nitrosodimethylamine			100	1/year	Grab
N-Nitrosodi-n-propylami			100	1/year	Grab
N-Nitrosodi-n-propylami	ne		100	I/year	Grab
Phenanthrene			100	1/year	Grab
Pyrene	****		100	1/year	Grab
1,2,4-Trichlorobenzene			100	1/year	Grab
Pesticides and PCB's					
Aldrin			10	1/year	Grab
Alpha-BHC			10	1/year	Grab
Beta-BHC			10	1/year	Grab
Delta-BHC			10	1/year	Grab
Gamma-BHC (Lindane)			10	l/year	Grab
Chlordane			10	1/year	Grab
4,4-DDT			10	1/year	Grab
4,4-DDE			10	1/year	Grab
4,4-DDD 4,4-DDD			10	1/year	Grab
Dieldrin			10	1/year	Grab
Alpha-Endosulfan			10	1/year	Grab
Beta-Endosulfan			10	1/year	Grab
Endosulfan Sulfate			10	1/year	Grab
			5		Grab
Endrin			10	l/year 1/year	Grab
Endrin Aldehyde				•	Grab
Heptachlor			10	1/year	
Heptachlor Epoxide			10 *	1/year	Grab Grab
PCB's (Total)		===	*	1/year	
PCB-1016	422			1/year	Grab

Effluent Characteristic	Discharge Limitations			Monitoring Requirements	
	lbs./day	other units	s (ug/l, unless state	ed)	
	Monthly	Monthly	Daily	Measurement	Sample
	Avg.	Avg.	<u>Max</u>	Frequency	Type
PCB-1221			*	1/year	Grab
PCB-1232			+	1/year	Grab
PCB-1242		***	*	1/year	Grab
PCB-1248			*	1/year	Grab
PCB-1254			*	1/year	Grab
PCB-1260			*	1/year	Grab
Toxaphene		700	10	1/year	Grab

^{*} This permit contained language prohibiting the discharge of PCB's.

XI. <u>ENFORCEMENT AND SURVEILLANCE ACTIONS:</u>

A) Inspections

A review of EDMS indicates the following inspections were performed during the period beginning November 2002 and ending November 2004 for this facility.

Date – May 20, 2004 Inspector(s) – Greg Fruge, LDEQ/Southwest Regional Office Findings and/or Violations:

A compliance evaluation inspection was done on this date and the following items were noted:

- 1. The facility personnel were calculating an average for pH and reporting it as a minimum and maximum on the discharge monitoring reports.
- 2. The pH was being analyzed more frequently than required by the permit, but some of those results were not being reported on the discharge monitoring reports.
- 3. The DMRs and lab reports for the period of April 2003 to April 2004 were reviewed. Gulf Coast Analytical conducts lab analysis for the facility.
- 4. A physical inspection did not reveal any apparent problems.

B) Compliance and/or Administrative Orders

A review of EDMS and TEMPO revealed the following enforcement actions(active) administered against this facility from the period beginning November 2002 through March 2005:

LDEQ Issuance:

Docket # - WE-L-04-0206

Issued - March 18, 2004

The letter informed the facility that on or about April 16, 2003 an inspection was conducted to determine compliance with the Louisiana Environmental Quality Act and supporting regulations. The inspection report, noting areas of concern was forwarded to the Enforcement Division. The letter informed the permittee that immediate steps needed to be taken to ensure compliance with all environmental regulations at their facility.

EPA Issuance: None

C) DMR Review

A review of the discharge monitoring reports for the period beginning November 2002 through November 2004 has revealed no permit violations.

XII. ADDITIONAL INFORMATION:

This facility has been downgraded from a major facility to a minor facility due to the nature of the discharge being strictly stormwater runoff from a capped landfill.

Biomonitoring was previously deleted as a parameter due to the fact that the discharge consists of only stormwater. Mass limits are not applied due to the intermittent nature of the discharge.

The parameter 2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD) was listed in the previous permit as a report requirement with the stipulations that the permittee may be allowed to discontinue the sampling and monitoring requirement after the second year, if the results are below the specified value for this parameter. The permittee requested removal of this parameter in the renewal application. An evaluation of the DMRs revealed that non-detect was reported for this parameter. Therefore, the parameter 2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD) will be removed from this permit.

Please be aware that the Department of Environmental Quality has completed the TMDLs for waterbodies located in the Ouachita River Basin. The Department of Environmental Quality reserves the right to impose more stringent discharge limitations and/or additional restrictions in the future to maintain the water quality integrity and the designated uses of the receiving water bodies based upon additional water quality studies and/or TMDLs. The DEQ reserves the right to modify or revoke and reissue this permit based upon any changes to established TMDLs for this discharge, or to accommodate for pollutant trading provisions in approved TMDL watersheds as requested by the permittee and/or as necessary to achieve compliance with water quality standards. Therefore, prior to upgrading or expanding this facility, the permittee should contact the Department to determine the status or the work being done to establish future effluent limitations and additional permit conditions.

The Monitoring Requirements, Sample Types, and Frequency of Sampling will be as follow:

Effluent Characteristics	Monitoring Require	irements	
	Measurement	<u>Sample</u>	
	Frequency	<u>Type</u>	
Flow	1/month	Estimate	
TOC	1/month	Grab	
Oil & Grease	1/month	Grab	
Ammonia (NH ₃ -N)	1/month	Grab	
Total Phenols (4AAP)	1/month	Grab	
Metals and Cyanide	1/month	Grab	
Volatile Compounds	1/year	Grab	
Acid Compounds	1/year	Grab	
Base Neutral Compounds	1/year	Grab	
Pesticides and PCB's	1/year	Grab	
pН	1/day	Grab	

Environmental Impact Questionnaire:

Applicant Comments/Responses (verbatim from applicant)

- 1. Have the potential and real adverse effects of the proposed facility been avoided to the maximum extent possible?
- 2. Does a cost benefit analysis of the environmental impact costs balanced against the social and economic benefits of the proposed facility demonstrate that the latter outweighs the former?
- 3. Are there alternative projects which would offer more protection to the environment than the proposed facility without unduly curtailing nonenvironmental benefits?

- 4. Are there alternative sites which would offer more protection to the environment than the proposed facility site without unduly curtailing nonenvironmental benefits?
- 5. Are there mitigating measures which would offer more protection to the environment than the facility as proposed without unduly curtailing nonenvironmental benefits?

This is an existing facility with no modifications to the site. The original IT questions were submitted with the initial permit; however, the permittee has updated their responses in the renewal application.

XIII. TENTATIVE DETERMINATION:

On the basis of preliminary staff review, the Department of Environmental Quality has made a tentative determination to reissue a permit for the discharge described in this Fact Sheet.

XIV. REFERENCES:

Louisiana Water Quality Management Plan, Vol. 8, Appendix A "Areawide Effluent Limitations Policy", Louisiana Department of Environmental Quality, 2005.

<u>Louisiana Water Quality Management Plan, Vol. 5, Part B, "Water Quality Inventory"</u>, Louisiana Department of Environmental Quality, 2002 and 2004.

<u>Louisiana Administrative Code, Title 33 - Environmental Quality, Part IX - Water Quality Regulations, Chapter 11 - "Louisiana Surface Water Quality Standards"</u>, Louisiana Department of Environmental Quality, 2006.

LA 2004 Integrated Report with FINAL EPA Additions, August 17, 2005.

Louisiana Administrative Code, Title 33 - Environmental Quality, Part IX - Water Quality Regulations, Chapter 23 - "The LPDES Program", Louisiana Department of Environmental Quality, 2006.

<u>Low-Flow Characteristics of Louisiana Streams</u>, Water Resources Technical Report No. 22, United States Department of the Interior, Geological Survey, 1980.

<u>Index to Surface Water Data in Louisiana</u>, Water Resources Basic Records Report No. 17, United States Department of the Interior, Geological Survey, 1989.

LPDES Permit Application to Discharge Wastewater, CECOS International, Inc., Calcasieu Facility, June 30, 2004.